



QuickSeam Cover Strip

1. Description

QuickSeam Cover Strip is a 152mm wide semi-cured rubber strip, designed to cover and seal batten bars used to mechanically anchor the membrane and strip in seams when additional protection is required and/or recommended (e.g. dung pit applications), as specified by Firestone specifications. The semi-cured EPDM strip layer is factory laminated to QuickSeam Tape.

2. Preparation

The EPDM geomembrane surfaces and/or compatible mating surfaces must be prepared with QuickPrime Plus, using a Quick-Scrubber tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

On sunny days greater than 20°C, place QuickSeam Cover Strip (prior to application) with release paper side up to prevent QuickSeam Cover strip from gaining too much heat.

QuickSeam Cover Strip is to be applied as per the Firestone specifications and details.

4. Coverage

In accordance with length of detail. Pieces must overlap a minimum of 75mm and extend a minimum of 75mm beyond critical points.

5. Characteristics

The Firestone QuickSeam Cover Strip is a rubber material with the following properties:

Technical	EPDM Flashing	QuickSeam Tape
• Base	EPDM	rubber polymers
• Color	black	black
• Solvents	none	none
• Solids(%)	100	100
• State	semi-cured	cured
• Thickness	1.0mm	0.9mm

6. Precautions

Take care when moving, transporting or handling to avoid sources of punctures and physical damage. Isolate waste products, such as petroleum products, greases, oils (mineral and vegetable) and animal fats from Firestone QuickSeam Cover Strip. As the product is semi-cured, QuickSeam Cover Strip has good chemical resistance.

Store in original unopened carton at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf life is expected to be 12 months, when stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures.